

**Continue**

17375553.805556 41558272729 17732163.323232 178868285624 109309276349 92659801258 24356256.803279 114505484655 27022672.571429 21064198.083333 28188854.714286 119041964744 25738382755 89513528992 78038078040 17892673.622222 13260695.444444 16222480.809524 53870323.416667 2924770970  
37104180.243243 25184487054 23812348.796296 48696829465 6257945736



Ego chainsaw instructions. Ego chainsaw customer service. Ego chainsaw problems. How to start ego chainsaw.

PANGE 28 3. Check the sharpness of the saw current cutting teeth. Causes and Prevention of the bribe operator (Fig. Check that the current is assembled correctly and correctly tensioned. 30) In the specified sides of the lateral plate and with the same length, as the ruffy cut can be obtained only when the depth meter all cutters are uniform. Page 31 To interrupt the current of the current 1. Readjust the current tension, following the section: "Adjusting the chain tension". A moment of discouragement during the operating operais of elapsed tools can result in serious personal injuries. If the operation is dusty, also use a dust. 36. Page 12 - , - If they occur situations that are not covered in this manual, use care and good judgment. Page 43 deputation of depth depth meter measurement 1. Failure to follow the warnings and instructions can result in a shock, incoming, and/or severe lesion. Use a grease syringe to lubricate weekly with the current -lubricant origin of the lubricating orifice (Fig. Specifications Specifications of the 350 mm Current Maninio Type of Current Type of 1.1 mm Type of Current 90px052x (Oregon) BAR BAR TYPE 144MLEA041 (Oregon) Chain Tank 150 ml Weight (no battery, current sheath) 3.76 kg no sound power measured the noise of 96.73 dB (a) In the ear of operator L 85.73 dB (a) k = 2.5 dB (a) does not discard the packaging material that you have carefully inspected and satisfactorily operated the tool. 6 o During the operation of mountains can cause tangling your clothes or body with the current. 2. Before starting the saw, make sure the saw is not coming into contact with anything. 11A ) Align the battery ribs with the assembly slots on the door of the streamlined battery. Tie Current cutters, following the section: & #039;How sharpening the cutters. Rotate the current tensioning botan in the front direction, as much as it will be. Page 10 Avanations of Serra de Cara & #039;, - & #039; . Keep all parts of the body away from Serra Serra When the current saw is operating. Security Instructions This Panigan describes and describes security

samples that may appear in this product. The security warning indicates a potential risk of personal injury. , - , - Å Ä Ä SERRA in a flat and firm surface, keep the mountain firmly with both hands. Page 13 Kickback is the result of misuse of tools and/or procedures or incorrect operational conditions and can be avoided by taking due precautions as given below: Firm, with thumbs and fingers circulating the highlights of the current saw, with the two hands in the mountains and position your body and brain to allow you to resist the bribe ... Read the risk of the risk of lesion £ o, the user should read the operator's operator manual. Blocking button helps prevent accidental or authorized active activation of the trigger switch. Warning: Always remove the battery from the current saw during the work intervals and after finishing the work. , - , - Push the chain braces' rainfall in the front of the mountain. Move the stream of the current away from the cutting area and release the trigger switch to interrupt the stream. 1, 2, 3 and 4) The braces can occur when the nose ... Place the guide bar in the mounting surface sliding the slot from the bar on the alignment flanges, making sure that the tensan adjustment pin It is inserted into the lower orifier in the origin in hell in the bar tail (Fig. 24): Bucking is cutting a trunk into lengths. Push the chain braces brake rank to the front of the brake position to wrap the current brake (Fig. Damage. Warning: Always wear gloves when handling the saw current; these components are not and may contain the burrs. The depth of clearance of meters of 0.6 mm. 5. Motore and remove the battery before adjusting the current tension. The trigger switch turns on and off the current saw. Page 36 Bucking A trunk (Fig. The toothed wheel should be lubricated from the guide bar weekly with a grease syringe to extend the life of the bar. to try to assemble and operate. -Current installed for TRANSIDA. A proper operating mother brake interrupts the movement of the current immediately. For example: use current saw to cut plastic, masonry or materials Construction of wood. Made to provide the best possible reliability and performance. SAIN SABOLS The purpose of the safety of Sanbos is attracting its attention to possible dangers. Packaging List Name Quantity of the Peäo ... Warning: To avoid serious personal injuries, remove the battery from the mountain range Current before inspecting, cleaning or performing maintenance. Å € , - Only cut wood. Mother with wireless wireless saw of the wireless chain of 56V ... Gosuy, the oily highly slippery, causing loss of control. The use of this product with damaged or absent pens may result in serious personal injuries. Page 25 7. , - , - Å œ If any Peäo is damaged or absent, contact ego customer service for welfare. Page 24 4. Instead, push those pushed or dragged with heavy equipment å € ight and then the cuts. , - , - not fell by the elderly wires or buildings. Do not do this can result in objects being thrown into your eyes and other possible serious injuries. Page 8 Personal Security å , - , - Warning, note what is doing and use the Sense when operating an elf tool. Do not use an ethical tool while you are tired or under the influence of drugs, Å nalcool or medications. PAGINE 35 35 Undercut, with mark, makes the notch 1/3 of the divestock of the river, perpendicular to the direction of the fall, 50 mm moving away, as illustrated in Fig. Warning: Inadequate chain sharpness increases bribery potential. Sadbole warnings do not eliminate no danger. Page 30 Starting/interrupting the current saw before starting the current saw: 1. Fault the lowest direction of the horizontal cut of fall first. Page 41 How to sharpen the upper plate of the cutters, be careful to archive all cutters (fig. Check the noise of the tank and fill the tank as needed. Description Specification 3127499000 tank lid 3402502000 Å³le Filter 3127500000 Chain Sheath 3705657000 BAR GUIDE 350 mm 3810637000 CHAIN SAW 28238600 SIDE COVER SET 5610042000 ST4.2 X 19 3127504000 FRONT WATER 5610011000 SCREWS ST2.9X10 3421169000 : Failure to replace or repair a damaged current can cause severe injuries. Remember that a fraction of a fraction of a fraction of a fraction A failure of a: the second is sufficient to inflict serious injuries. Chain maintenance warning: Remove the battery before performing any maintenance; in severe personal injuries. Use only low quiet chains in this mountain range. If the current brake is not working properly, use the current saw to be repaired by a qualified service. It must be depressed before the trigger switch can be activated. 3. Place the new saw current in a loop in a flat surface and straighten any rounds (Fig. Save all warnings and instructions for future reference. When possible, the trunk should be lifted and supported by use of members, trunks or calen. and the rear high with the right. 9). Security and explanations with them deserve their care and careful understandings. Assembly Warning: If any peäo is damaged or absent, do not operate this product to the replaced by replaced. Page 39 Replacing Bar and Chain Warning: Before performing any maintenance, make sure the battery is removed. ¢ - , - Start the current saw. Warning: Not try to modify this product or create recommended access to use with this current saw. The instructions and warnings that they are not in substitute for adequate accident prevention measures. 7) Chain Kickback Brake Bra "Botion Botan Botan Trigger Key Chain Guide Battery Liberate the butch butch tank lid ejection Window mechanism contact process cross-cut processing process to overthrow or register in lengths. The index read all the instructions ..... 3 SABOLS OF SAFETY. 4. The inspection window of the å³le provides a display in the noisy of the Å³le. This will help to avoid tightening the 50 mm saw current ... Page 34 , - , - Å œ It has not fallen into the leaning of extreme or large widely members with limbs Rota, loose peel or hollow trunks. For three years from the date of original retail purchase, the battery and the Power+ System Ego charger are guaranteed against defects in material or work. Carefully pour the bar and the chain of the tank into the tank. The current tensioning screw allows precise adjustment of the current tension with a manual slit switch. 15 and 16) Warning: Fully charge the battery before its first use. Penão 9 - Storing tools for the scope of children's scope and will not allow people to familiarize with the Electrical Tool or these instructions to operate the Electrical tool. Defective product will receive free repair. The current brake makes the bribery brake high. See the section: å € œSubstimate bar and chain € ... 3180. Page 7 Warning of the General Energy tool! Read all warnings and instruments of Page 33 recommendation that the enjoyment for the first time should, as a mother, cutting logs a mountain range or berä. Å ¢ - ... Page 1 Operation Manual of 56V Opening Woolas Model Model CS1400E Warning: To reduce the risk of lesion, the user must read and understand the Operation Manual before using this product. Make sure the side cover botan is loose. The tools are dangerous in the mothers of usual uses not trained. Page 6 two hands always use two hands when operating the retention stream, not exposing, not use in the rain or outdoors while it rains is raining. ¢ - , - , - , - opaque current. Page 16 GLINARE OF TERMS AUTOMONIC OILERAGE: A system that automatically lubricates the guide bar and saw current. The filter at the opening of the tank lid allows the å³le to slowly penetrate the tank; ... is not involved in the ¢ - , - , - , - Å œ Å ¾ Possible contact of current and customer service. 15) 1. NOTICE OF OPERATION: NOT allow familiarity with this product to make it careless. The depth meter should be kept at a 0.6 mm clearance, as shown in Fig. Warning: Always use safety insurance or insurance with lateral shields during the operating tool of the tool or by blowing dust. Warning: Always use ocular protection with side shields. Danger: People with electrical devices, such as pacemakers, should consult their moms before using this product. 56V Saw Ion Ion Litan Ion Chineha ... Bucking Pikes: The tooth or pointed teeth for use when dropping or blocking to rotate the saw and maintain position during sawing. Read all instructions! This current saw has many resources to make its use more pleasant and pleasant. Number of phone: 1300 000 ego (1300 000 346). Page 37 - When the log is supported by the two shades supported by both ends, cut 1/3 of this over -excess diameter. Failure to meet this warning may result in personal injuries Thus, the operator must be ready to control the lock when cutting to the bottom edge of the bar and the push when cutting the upper edge. Guarantee of services for five years from the date of original retail purchase, this product of the ego is guaranteed against defects in material or work. Contact EGO customer service for welfare. The side cover lid the cuddly wheel of the current and holds the sidebar of the sidebar lock/unlock the release botan of the side lid battery press to release the tool battery. Rotate the current tensioning botan in the hourly direction to tender the current. 14). Page 32 The proper squeeze in the highs with the thumb of åferences-a-¾ below the gloves without sliding for the mother and protection. The tank of the å³le seals the tank of å³eus. Penina 29 To install/remove the battery (Fig. Then, the 1st Overbuck cut (1/3 of diary) to avoid chipping the finished cut, by undergoing the lower 2/3 to meet the first cut ( Fig. This cropping current will provide tuition fees when maintained properly. So that the tank lid is facing up. Use current saw for purposes. To ensure that your pion is firm and your weight be evenly distributed in the two pages to install (fig. Force tool or battery -operated (wireless) forms. Warning: Always wear gloves by handling the bar and current; these components are not overdue and may contain burrs. 1. This manual contains Important Information on Assembly, Operation and Security Maintenance of its current saw. and It can cause excessive engine speed during cutting, which may result in serious motor damage. If you have any problem that you can not remedy easily, contact the EGO Customer Care Center 1300 000 EGO (1300 000 346). Security, performance and reliability received a mother priority in the design of this product, facilitating the maintenance and operation. MAINTENANCE NOTICE: Upon answering, use only interplains replacement. Page 11 - Keep the highs dried, clean and free of å³le and grease. , - debris, preventing complete clean debris of the movement of the current brake mechanism. 8. Save these instructions for future reference. Describe you know your current saw (Fig. Put the current links in the grooves of the bar.